

Receiver
From

 Society
 Reference
 Address
 Phone
 Fax
 E-mail

Item n° :

1D1K11BX3

Model :

NKM-G 32-125.1/140/A/BAQE/0,25/4

Pump data

Impeller size (mm) : 140

MEI ≥ 0,40

Pressure rating : PN 16

Min. fluid temperature : 14 °F

Max. fluid temperature : 284 °F

Max. Ambient temperature : 104 °F

Requested data

Flow : 0/00 US g.p.m.

Head : 0/00 m

Fluid (%) : Water, pure

Fluid Temperature : 68 °F

 Density : 62/322 lb/ft³

 Kinematic viscosity : 1/0818E-5 ft²/s

Vapor pressure : 2/34 kPa

Real duty point

Flow :

Head :

NPSH :

Shaft power P2 :

Efficiency :

Materials

Pump body : Cast iron 250 UNI ISO 185

Support : Cast iron 250 UNI ISO 185



Impeller : Cast iron 250 UNI ISO 185

Mechanical seal : SEE "SHAFT SEAL" SECTION

OR ring : Ethylene propylene (EPDM)

Pump shaft : AISI 304 X5 Cr Ni 1810 UNI 6900/71

Motor : AISI 304 X5 Cr Ni 1810 UNI 6900/71

Curve tolerance according to ISO 9906

Shaft seal

 Type : Rubber
 Stationary part : Carbon
 Rotating part : Silicon carbide
 Elastomer : EPDM

Motor data

 Nominal power P2 : 0/25 kW
 Rated speed : 1400 rpm
 Rated voltage : 3~ 230 V / 400 V 50 Hz
 Nominal current : 1/6 / 0/9 A
 Degree of protection : IP 55

Weight : 33 kg

Dimensions in mm

Dimension	Value	Dimension	Value	Dimension	Value
A	80	H2	140	X	100
B	50	L	201		
DNA	50	M1	100		
DNM	32	M2	70		
F	208	N1	190		
G	234	N2	140		
H1	112	S1	M10		

Pump connection

Suction side : DN 50 / PN 16

Discharge side : DN 32 / PN 16