

**Receiver**
**From**

 Society  
 Reference  
 Address  
 Phone  
 Fax  
 E-mail

**Item n° :**

1D1K11B3U

**Model :**

NKP-G 32-125.1/102/A/BAQE/0,75/2 IE3

**Pump data**

Impeller size (mm) : 102

MEI ≥ 0,40

Pressure rating : PN 16

Min. fluid temperature : 14 °F

Max. fluid temperature : 284 °F

Max. Ambient temperature : 104 °F

**Requested data**

Flow : 0/00 US g.p.m.

Head : 0/00 m

Fluid (%) : Water, pure

Fluid Temperature : 68 °F

 Density : 62/322 lb/ft<sup>3</sup>

 Kinematic viscosity : 1/0818E-5 ft<sup>2</sup>/s

Vapor pressure : 2/34 kPa

**Real duty point**

Flow :

Head :

NPSH :

Shaft power P2 :

Efficiency :

**Materials**

Pump body : Cast iron 250 UNI ISO 185

Support : Cast iron 250 UNI ISO 185



Impeller : Cast iron 250 UNI ISO 185

Mechanical seal : SEE "SHAFT SEAL" SECTION

OR ring : Ethylene propylene (EPDM)

Pump shaft : AISI 304 X5 Cr Ni 1810 UNI 6900/71

Motor : AISI 304 X5 Cr Ni 1810 UNI 6900/71

**Curve tolerance according to ISO 9906**

**Shaft seal**

 Type : Rubber  
 Stationary part : Carbon  
 Rotating part : Silicon carbide  
 Elastomer : EPDM

**Motor data**

 Nominal power P2 : 0/75 kW  
 Rated speed : 2810 rpm  
 Rated voltage : 3~ 400 V / 230 V 50 Hz  
 Nominal current : 1/62 / 2/81 A  
 Degree of protection : IP 55

**Weight :** 35 kg

**Dimensions in mm**

Dimension	Value	Dimension	Value	Dimension	Value
A	80	H2	140	X	100
B	50	L	226		
DNA	50	M1	100		
DNM	32	M2	70		
F	234	N1	190		
G	234	N2	140		
H1	112	S1	M10		

**Pump connection**

Suction side : DN 50 / PN 16

Discharge side : DN 32 / PN 16