

Receiver
From

Society
 Reference
 Address
 Phone
 Fax
 E-mail

Item n° :

60120034

Model :

EUROPRO 75 M

Pump data

Pressure rating : 2,5 bar (250 kPa)
 Min. fluid temperature : 32 °F
 Max. fluid temperature : 140 °F
 Max. Ambient temperature : 122 °F

Requested data



Flow : 0/00 US g.p.m.
 Head : 0/00 m
 Fluid : Water, pure
 Fluid Temperature : 68 °F
 Density : 62/322 lb/ft³
 Kinematic viscosity : 1/0818E-5 ft²/s
 Vapor pressure : 2/34 kPa

Hydraulic data (duty point)

Flow :
 Head :

Materials

Pump body	Reinforced technopolymer
Impeller	Reinforced technopolymer
Diffuser	Reinforced technopolymer
Filter	Technopolymer
Mechanical seal	Carbon/Alumina/NBR/AISI316
Filter cover	Poly carbonate
O-ring	NBR

Curve tolerance according to ISO 9906

Weight : 12/1 kg

Motor data

Motor brand : DAB
 Nominal power P2 : 0/5 kW
 Rated speed : 2900 rpm
 Rated voltage : 1~ 220-240 V 50 Hz
 Nominal current : 5 A
 Degree of protection : IP 55

Dimensions in mm

A	552	I	11
B	242	L	6/5
C	245		
D	257		
DNA	2" G		
DNM	2" G		
E	265		
F	220		
G	150		
H	351		
H1	222		
H2	314		

Pump connection

Suction side : 2" G / 2,5 bar (250 kPa)
 Discharge side : 2" G / 2,5 bar (250 kPa)