

Receiver
From

 Society
 Reference
 Address
 Phone
 Fax
 E-mail

Item n° :

60141714

Model :

DRENAG 3000 T-NA

Pump data

 Free passage : 5 mm
 Pressure rating :
 Min. fluid temperature : 32 °F
 Max. fluid temperature : 104 °F
 Max. Ambient temperature :

Requested data

 Flow : 0 US g.p.m.
 Head : 0 m
 Fluid : Water, pure
 Fluid Temperature : 68 °F
 Density : 62/322 lb/ft³
 Kinematic viscosity : 1/0818E-5 ft²/s
 Vapor pressure : 2/337 kPa

Hydraulic data (duty point)

 Flow :
 Head :



Materials

 Top cover : Anodized aluminium
 Impeller : Cast iron (EN GJL 200)
 Pump body : Cast iron (EN GJL 200)
 Mechanical seal motor side : Carbon/Alumina
 Mechanical seal pump side : SiC/SiC
 Motor body : Anodized aluminium
 OR ring : NBR

Motor data

 Motor brand : DAB
 Nominal power P2 : 2/2 kW
 Rated speed : 2800 rpm
 Rated voltage : 3~ 400 V
 Nominal current : 6/2 A
 Degree of protection : IP 68

50 Hz

Curve tolerance according to ISO 9906

Weight : 26 kg

Dimensions in mm

Dimension	Value				
A	550				
B	215				
C	112				
D	110				
E	2" 1/2 G				

Pump connection

 Suction side : /
 Discharge side : 2" 1/2 G / 12 bar (1200 KPa)