	<b>Product Information</b>  <b>CDL10-5</b>	Manufacturer	CNP
		Address	Yuhang District, Hangzhou, Zhejiang,
Project Name		Contact	86-571-88637351
		Date	2022/03/05
Item NO		Client Name	DPA
		Client Addr.	
		Contacts	Alireza
		Contact	

Part NO.	1100088576
----------	------------

Product Picture	Note
	<p>Non-self-priming vertical multistage centrifugal pump, the motor shaft through the coupling shaft is coupled directly to the impeller vanes made of stainless steel plate stamping and welding or precision casting made of stainless steel, the pump inlet and outlet of the pump bottom at the same line (it can be equipped with IEC or NEMA motors).</p>

<b>technology</b>	
Pump rotator speed	2900
Nameplate standards	CE
Pump version	2
<b>Material</b>	
Impeller	316
Rubber code	E
Inlet&outlet chamber	316L
Material Code	L
<b>Installation</b>	
Connection Code	F
Maximum Pressure/Temperatu	22 bar / 120
Maximum Pressure/Temperatu	22bar / -15
Flange Standard	DIN
Pressure Class	PN25
Inlet & outlet	DN40
<b>Medium</b>	
Medium Temperature normal	-15+70
Medium Temperature high t	-15+120
Maximum Environment Temper	40
<b>Motor</b>	
Number of Motor Phase	Three Phase
Protection Class	IP55
Insulation Class	F
Motor Power	2.2KW
Power Frequency	50HZ
Rated Voltage (V)	220/380V
Rated Current (A)	7.9/4.6A
Energy Efficiency Level	IE3
<b>Seal</b>	
Mechanical Seal	CDLA-16/WBF16
<b>Others</b>	
Weight (kg)	53




# Performance Curve CDL10-5

Manufacturer	CNP
Address	Yuhang District, Hangzhou, Zhejiang,
Contact	86-571-88637351
Date	2022/03/05
Client Name	DPA
Client Addr.	
Contacts	Alireza
Contact	

Project Name

Item NO

The hydraulic performance curve have been tested with Clean Water at 20°C, density 1000kg/m<sup>3</sup>, and at 1bar atmospheric pressure. ISO99062012 Grade 3B





## Pump Technical Parameters CDL10-5


Manufacturer	CNP
Address	Yuhang District, Hangzhou, Zhejiang,
Contact	86-571-88637351
Date	2022/03/05
Client Name	DPA
Client Addr.	
Contacts	Alireza
Contact	

### Rated parameters

Pump model	CDL10-5
Part NO.	1100088576
Rated flow (m <sup>3</sup> /h)	10
Rated head (m)	39
Rated efficiency (%)	67
Power (kW)	1.59
NPSHr (m)	2
Speed (rpm)	2900
Max impeller diameter (mm)	92.3

### Medium

Pumped medium	Clean Water
Working temperature (°C)	20
Medium density (kg/m <sup>3</sup> )	1000
Viscosity (mm <sup>2</sup> /s)	1






**Structure picture**  
**CDL10-5**

Manufacturer	CNP
Address	Yuhang District, Hangzhou, Zhejiang,
Contact	86-571-88637351
Date	2022/03/05
Client Name	DPA
Client Addr.	
Contacts	Alireza
Contact	

Project Name

Item NO





**Dimension Drawing**  
**CDL10-5**

Manufacturer	CNP
Address	Yuhang District, Hangzhou, Zhejiang,
Contact	86-571-88637351
Date	2022/03/05
Client Name	DPA
Client Addr.	
Contacts	Alireza
Contact	

Project Name

Item NO

