	Product Information	Manufacturer	CNP	
	Product information	Address	Yuhang District, Hangzhou, Zhejiang,	
CND	500WQ2000-9-75(I)		86-571-88637351	
	300WQ2000-3-73(I)	Date	2022/03/09	
Project Name	Project Name		DPA	
Project Name		Client Addr.		
Item NO		Contacts	Alireza	
ILEIII NO		Contact		

Part NO.	500WQ2000-9-75	
Product Picture		Note
		The sewage submersible pump is composed of two parts: the motor and the pump. The two are separated by an oil chamber and a mechanical seal assembly. Divided into fixed automatic coupling installation and mobile installation
technology		

Material

Pump rotator speed

Nameplate standards

Impeller HT200
Pump shaft 20cr13
Rubber code P
Pump case HT200

983

CE

Installation

Connection Code

Maximum Pressure/Temperatu 10bar/40
Flange Standard DIN
Pressure Class PN10

Medium

Medium Temperature40Maximum diameter of partic120Maximum Environment Temper40

Structure dimension

Standard caliber DN

Outlet Diameter DN500

Motor

Number of Motor Phase Three Phase
Protection Class IP68
Insulation Class F
Motor Power 75
Power Frequency 50HZ
Rated Voltage (V) 380V
Rated Current (A) 138

Starting mode Star delta boot


Seal

Mechanical Seal H-70

Others

Weight (kg) 1522


	Performance Curve	Manufacturer	CNP
	remorniance curve	Address	Yuhang District, Hangzhou, Zhejiang,
COND	500WQ2000-9-75(I)		86-571-88637351
	3000042000-9-73(1)	Date	2022/03/09
Project Name	Project Name		DPA
Project Name			
Item NO		Contacts	Alireza
Itelli NO		Contact	




	Pump Technical Parameters	Manufacturer	CNP
	Fullip reclinical rataliteters	Address	Yuhang District, Hangzhou, Zhejiang,
COND	500WQ2000-9-75(I)	Contact	86-571-88637351
	300 W Q 2000-3-73(1)	Date	2022/03/09
Project Name	Project Name		DPA
Project Name		Client Addr.	
Item NO		Contacts	Alireza
Item NO		Contact	

Rated parameters	
Pump model	500WQ2000-9-75(I)
Part NO.	500WQ2000-9-75
Rated flow (m³/h)	2000
Rated head (m)	9
Rated efficiency (%)	72.8
Power (kW)	67.4
NPSHr (m)	2
Speed (rpm)	983

Medium	
Pumped medium	Clean Water
Working temperature (°C)	20
Medium density (kg/m³)	1000
Viscosity (mm²/s)	1
	-








CNP Nanfang Zhongjin Environment Co., Ltd.

SECTIONAL DRAWING		No.		No.		
TYPE subi	mersible sewage p	ump	MODE	L WQ-	-55/7	75kW



No.	names of parts	number	material	No.	names of parts	number	material
1	cab1e	2	YCW	54	shaft	1	2Cr13
6	cable sleeve	2	HT200	55	rotor	1	
50	top cover	1	HT200	56	stator	1	
58	cable transit board	1	Q235	52B	lower bearing	2	
64	base	1	HT200	36	machine oil 32#		
65	Water proof cover	1	Q235	26	framework oil seal	3	NBRI-2
62	Bearing cover	1	HT200	140	oil filler plug	2	SUS304
25	mechanical seal	1	Carbon/SIC	71	Shaft sleeve	2	1Cr13
30	oil lift	1		21	impeller	1	HT200
60	lower cover	1	HT200	22	water inlet cover	1	HT200
29	Casingtop cover	1	HT200	34	Neck ring	2	HT200
20	casing	1	HT200	94	guiding	1	Q235Steel board
46	Air release bolt	2	SUS304	92	pipe	2	SUS304(unaffiliated)
510	lift chain	1	SUS304	93	guide hook	1	QT600
10	Cable lockblock	2	HT200	91	water outlet base	1	HT200
72	eye bolt	2	45#(forging galvanized)	99	coupling flange	1	HT200
52A	upper bearing	1		96	guide plug	2	HT150
53	Mini-thermalprotector	1		0			

Nanfang Zhongjin Environment CO., LTD.

unit: mm

	Installation picture	Manufacturer	CNP
	installation picture		Yuhang District, Hangzhou, Zhejiang,
CIND	500WQ2000-9-75(I)	Contact	86-571-88637351
CIAL	300WQ2000-3-73(I)		2022/03/09
Project Name		Client Name	DPA
Project Name		Client Addr.	
Item NO		Contacts	Alireza
item NO		Contact	

