	Product Information	Manufacturer	CNP
		Address	Yuhang District, Hangzhou, Zhejiang,
CNP	CDLK42-110/11-2	Contact	86-571-88637351
DOI W	CDLR42-110/11-2	Date	2022/07/19
Project Name		Client Name	DPA
		Client Addr.	
Item NO		Contacts	Alireza
		Contact	

Part NO.	1100057352	
Product Picture		Note
		Product introduction CDLK/CDLKF is non-self priming multi-stage centrifugal pump installed with standard motor. The motor shaft is directly connected with the pump shaft through coupling. The impellers and diffusers are made of stainless steel plate stamping and welding. In order to meet the requirement of installation depth of the water tank or vessel, it is possible to install cavity diffusers for changing length of the pump. Performance and advantages Compact structure Convenient maintenance Changeable installation depth

Nameplate parameters

flow 42 m³/h
head 217 m
Efficiency 71
speed 2900
number of stages 11

technology

Pump rotator speed 2900 Nameplate standards CE

Material

Impeller 304
Rubber code P
Material Code S

Medium

Medium Temperature normal -15°C+70°C

Medium Temperature high t -15°C+105°C

Maximum Environment Temper 40°C

Three Phase

Motor

Number of Motor Phase

Protection Class IP55
Insulation Class F
Motor Power 45KWKW
Power Frequency 50HZ
Rated Voltage (V) 380V
Rated Current (A) 82.7A
Energy Efficiency Level IE3


Seal

Mechanical Seal CDLA-22/WSF14

Others

Weight (kg) 388


	Performance Curve	Manufacturer	CNP
		Address	Yuhang District, Hangzhou, Zhejiang,
CONP	CDLK42-110/11-2	Contact	86-571-88637351
DOI VI	CDLR42-110/11-2	Date	2022/07/19
Project Name		Client Name	DPA
		Client Addr.	
Item NO		Contacts	Alireza
		Contact	



	Pump Technical Parameters	Manufacturer	CNP
	ramp recimical raidineters	Address	Yuhang District, Hangzhou, Zhejiang,
CONP	CDLK42-110/11-2	Contact	86-571-88637351
D OITH	CDLR42-110/11-2	Date	2022/07/19
Project Name		Client Name	DPA
		Client Addr.	
Item NO		Contacts	Alireza
		Contact	

Rated parameters			
Pump model	CDLK42-110/11-2		
Part NO.	1100057352		
Rated flow	42 m³/h		
Rated head	217 m		
Rated efficiency (%)	71		
Power (kW)	35		
NPSHr (m)	3		
Speed (rpm)	2900		
Max impeller diameter (mm)	136		

Medium	
Pumped medium	Clean Water
Working temperature (°C)	20
Medium density (kg/m³)	1000
Viscosity (mm²/s)	1





GCNP	Physical picture	Manufacturer	CNP
		Address	Yuhang District, Hangzhou, Zhejiang,
	CDLK42-110/11-2	Contact	86-571-88637351
		Date	2022/07/19
Project Name		Client Name	DPA
		Client Addr.	
Item NO		Contacts	Alireza
		Contact	

