



**Product Information**  
**CDM15-5**

Manufacturer	CNP
Address	Yuhang District, Hangzhou, Zhejiang,
Contact	86-571-88637351
Date	2022/07/26
Client Name	DPA
Client Addr.	
Contacts	Alireza
Contact	

**Project Name**

**Item NO**

Part NO. 1100090764

Product Picture

Note



CDM/CDMF pumps are new generation, high efficiency, non-self-priming vertical multistage centrifugal pumps (Abbr. as pumps). It referred to European standard, adopted entirely new industrial design, efficiency achieved  $MEI \geq 0.7$ . It is energy saving, low noise, environment friendly, compact design, beautiful shape, light weight, easy for service, high reliability.

**Nameplate parameters**

flow	15 m <sup>3</sup> /h
head	58 m
Efficiency	71
speed	2900
number of stages	5

**technology**

Pump rotator speed	2900
Nameplate standards	CE
Pump version	2

**Material**

Impeller	304
Rubber code	P
Inlet&outlet chamber	304
Material Code	S

**Installation**


Connection Code	F
Maximum Pressure/Temperatu	22 bar/120 °C
Maximum Pressure/Temperatu	22 bar/-15 °C
Flange Standard	DIN
Pressure Class	PN25
Inlet & outlet	DN50

**Medium**

Medium Temperature normal	-15°C+70°C
Medium Temperature high t	-15°C+120°C
Maximum Environment Temper	40°C

**Motor**

Number of Motor Phase	Three Phase
Protection Class	IP55
Insulation Class	F
Motor Power	4KW
Power Frequency	50Hz
Rated Voltage (V)	380V
Rated Current (A)	7.8A
Energy Efficiency Level	IE3

	<b>Product Information</b>  <b>CDM15-5</b>	Manufacturer	CNP
		Address	Yuhang District, Hangzhou, Zhejiang,
		Contact	86-571-88637351
		Date	2022/07/26
<b>Project Name</b>		Client Name	DPA
		Client Addr.	
<b>Item NO</b>		Contacts	Alireza
		Contact	

**Seal**

Mechanical Seal                      CDLA-16/WBF14

**Others**

Weight (kg)                                61





# Performance Curve


## CDM15-5

Manufacturer	CNP
Address	Yuhang District, Hangzhou, Zhejiang,
Contact	86-571-88637351
Date	2022/07/26
Client Name	DPA
Client Addr.	
Contacts	Alireza
Contact	

Project Name

Item NO

The hydraulic performance curve have been tested with Clean Water at 20°C, density 1000kg/m<sup>3</sup>, and at 1bar atmospherical pressure. GB32162016 Grande 3B





## Pump Technical Parameters

### CDM15-5


Manufacturer	CNP
Address	Yuhang District, Hangzhou, Zhejiang,
Contact	86-571-88637351
Date	2022/07/26
Client Name	DPA
Client Addr.	
Contacts	Alireza
Contact	

### Rated parameters

Pump model	CDM15-5
Part NO.	1100090764
Rated flow	15 m <sup>3</sup> /h
Rated head	58 m
Rated efficiency (%)	71
Power (kW)	3.31
NPSHr (m)	1.8
Speed (rpm)	2900
Max impeller diameter (mm)	105

### Medium

Pumped medium	Clean Water
Working temperature (°C)	20
Medium density (kg/m <sup>3</sup> )	1000
Viscosity (mm <sup>2</sup> /s)	1






**Structure picture**  
**CDM15-5**

Manufacturer	CNP
Address	Yuhang District, Hangzhou, Zhejiang,
Contact	86-571-88637351
Date	2022/07/26
Client Name	DPA
Client Addr.	
Contacts	Alireza
Contact	

Project Name

Item NO





**Physical picture**  
**CDM15-5**

Manufacturer	CNP
Address	Yuhang District, Hangzhou, Zhejiang,
Contact	86-571-88637351
Date	2022/07/26
Client Name	DPA
Client Addr.	
Contacts	Alireza
Contact	

**Project Name**

**Item NO**

